

| ECOISO® SPL | ECOISO® QUADCORK OUTLINE |

Panels do not include mounting accessories (contact glue sold separately)

Mark the measurements of the existent surface (wall or ceiling) where you want to install the panel with a paper thin reference adhesive tape.

Prior to application, always clean all surfaces before applying any glue ensuring them free of dust or grease.

To ensure maximum adhesion strength do not reposition, so measure twice and glue only once.

On a workbench, apply contact glue (1 liter per sqm on both gluing surfaces) on the back of the panel all over the surface homogeneously.

In the area previously marked apply contact glue similarly as you did before on the panel ...homogeneously.

Now center the panel with the marks and press it firmly and homogeneously during the mounting glue's curing time, average approx. time 2 hours.

For ceiling panels temporary auxiliary supporting bars (anchors) between the floor and the center areas of the panel, can be used; while taking extra care to always use a protective thick and enough dense & clean material like foam (or a dense pillow) between the panel and the anchors to ensure not to damage panel surfaces. Between the anchor and the floor a protective material like a simple piece of wood or dense foam also should be used to protect floor finishings.

NOTICE: Adhesive time is dependant on the weight of the panel to glue. Always consult the mounting or contact glue specifications. Adhesive gluing times can vary with humidity and temperature. Make sure that the room's temperature and humidity are within the acceptable product values available on our website.

During application and the gluing phase ensure an abundant and proper air ventilation of the room as glues can release solvents and some odors with it. The usage of masks with recommended filter type are advised.

